

L5CLAMP-CNL-E2B



KwikClamp™ Hanger for 7/8 in coaxial cable, double stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	1
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Maximum Stack Height	2
Height	159 mm 6.26 in
Width	45 mm 1.772 in
Length	32 mm 1.26 in
Compatible Diameter, maximum	28 mm 1.102 in
Compatible Diameter, minimum	26 mm 1.024 in
Nominal Size	7/8 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
----------------------	--------------------------------------

L5CLAMP-CNL-E2B

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Five times cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed 47 cm | 18.504 in

Width, packed 30.5 cm | 12.008 in

Length, packed 26 cm | 10.236 in

Included Hardware

Packaging quantity 100

Weight, gross 17 kg | 37.479 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power