


# L7CLAMP-CNL-E3B



KwikClamp™ Hanger for 1-5/8 in coaxial cable, triple stack, C-Channel compatible; includes hardware

## Product Classification

<b>Product Type</b>	Hanger kit
<b>Product Brand</b>	KwikClamp™
<b>Ordering Note</b>	ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box

## General Specifications

<b>Cables per Hanger</b>	1
<b>Color</b>	Black
<b>Hanger Type</b>	KwikClamp™ hanger
<b>Mounting</b>	Channel section 40 x 22 x 1.5 mm

## Dimensions

<b>Maximum Stack Height</b>	3
<b>Height</b>	282 mm   11.102 in
<b>Width</b>	69 mm   2.717 in
<b>Length</b>	44 mm   1.732 in
<b>Compatible Diameter, maximum</b>	50 mm   1.969 in
<b>Compatible Diameter, minimum</b>	48 mm   1.89 in
<b>Nominal Size</b>	1-5/8 in
<b>Hanger Spacing, maximum</b>	1.83 m   6.004 ft

## Electrical Specifications

<b>Return Loss Effect, maximum</b>	0.1 dB
<b>DTF Effect, maximum</b>	0.1 dB

## Material Specifications

<b>Material Type</b>	Engineered plastic   Stainless steel
----------------------	--------------------------------------

# L7CLAMP-CNL-E3B

---

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Corrosion Resistance, minimum with no degradation** ≥500 hours in salt spray chamber

**Environmental Strength Capability** Five times cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

## Packaging and Weights

**Height, packed** 101 cm | 39.764 in

**Width, packed** 71 cm | 27.953 in

**Length, packed** 81.3 cm | 32.008 in

**Included** Hardware

**Packaging quantity** 100

**Weight, gross** 38 kg | 83.776 lb

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power