F4-HMHM-5M5-D



D-CLASS HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male, 5.5 m

WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type SureFlex® D-CLASS, dynamic PIM

Product Brand HELIAX® | SureFlex®

Product Series RSJ4-50

General Specifications

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector A4.3-10 MaleInterface, Connector B4.3-10 Male

Specification Sheet Revision Level B

Dimensions

Length 5.5 m | 18.045 ft

Nominal Size 1/2 in

Logo Image



F4-HMHM-5M5-D



Electrical Specifications

3rd Order IMD Dynamic -119 dBm

3rd Order IMD Dynamic Test Method Two +43 dBm carriers per IEC 62037

DTF, Connector A -34 dB

DTF, Connector B -34 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.065	30.04
1700-2200 MHz	1.065	30.04
2200-2700 MHz	1.083	27.99
3400-3800 MHz	1.222	20.01

Jumper Assembly Sample Label





Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system