

# LS2-XMNM-W1-D

Base Product



D-CLASS LSF2-50 SureFlex® Jumper with interface types NEX10 Male and N Male with HELIAX® SureGuard weatherproofing on NEX10 side

## Product Classification

Product Type	Wireless transmission cable assembly
Product Series	LSF2-50

## General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	NEX10 Male
Interface, Connector B	N Male
Specification Sheet Revision Level	A
Variable Length	For custom lengths, contact your local ANDREW representative

## Dimensions

Nominal Size	3/8 in
--------------	--------

## Logo Image

# LS2-XMNM-W1-D



## Electrical Specifications

3rd Order IMD Dynamic	-119 dBm
3rd Order IMD Dynamic Test Method	Two +43 dBm carriers per IEC 62037

## VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-970 MHz	1.065	30
1700-2200 MHz	1.065	30
2200-2700 MHz	1.083	28
3400-3800 MHz	1.222	20
4000-6000 MHz	1.222	20

## Jumper Assembly Sample Label

# LS2-XMNM-W1-D



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition