## **VSR-TS-B**



## V-Stabilizer™ for a Tower, small leg size (2–8 in)

## **Product Classification**

Product Type Reinforcement kit

General Specifications

Mounting Angle 60°, 203.2 mm (8 in) | Angle 90°, 152.4 mm (6 in) | Straight or tapered legs up to 203.2

mm (8 in) OD

Pipe, quantity 0

Tower Taper Non-tapered | Tapered

**Dimensions** 

 $\textbf{Face Width} \hspace{1.5cm} 4.42 \hspace{.1cm} \text{m} \hspace{.1cm} | \hspace{.1cm} 14.5 \hspace{.1cm} \text{ft}$ 

**Length** 1,206.5 mm | 47.5 in

Mounting Diameter, maximum 203.2 mm | 8 in

**Mounting Diameter, minimum** 50.8 mm | 2 in

Material Specifications

Material Type Hot dip galvanized steel

Packaging and Weights

Included Clamps | Legs

Packaging quantity 1

**Weight, net** 56.88 kg | 125.4 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted



## VSR-TS-B

UK-ROHS

Compliant/Exempted

