

KVVSS-65A-3XKIT



Tri-sector solution that includes 3 KVVSS-65A-R3-V1 antennas and mounting kit to install them on a pipe

- Suitable for attachment to 3.5-6.5 in or 89-165 mm outer diameter pipe
- Compatible with canister concealment shrouds with inner diameter > 23.5 in (597mm)
- Minimum shroud diameter is the same for all applicable pipe diameters

General Specifications

Band	Multiband
Performance Note	Outdoor usage
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	12
RF Connector Quantity, mid band	12
RF Connector Quantity, low band	6
RF Connector Quantity, total	30

Dimensions

Net Weight, with mounting kit 107 kg | 235.894 lb

Electrical Specifications

Operating Frequency Band 1695 – 2690 MHz | 3100 – 4200 MHz | 617 – 960 MHz

Packaging and Weights

Width, packed	601 mm 23.661 in
Depth, packed	1027 mm 40.433 in
Length, packed	1667 mm 65.63 in
Weight, gross	135.5 kg 298.726 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance

KVVSS-65A-3XKIT

ROHS Compliant

UK-ROHS Compliant



* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance